


## General info

## Outdoor - Floor lamps



|              |                        |
|--------------|------------------------|
| Ean          | 8021696293424          |
| Item         | DJAMBE PT D74 NERO     |
| Installation | Floor lamps            |
| Guarantee    | 5 years                |
| Gross weight | 9.7 kg                 |
| Volume       | 0.16544 m <sup>3</sup> |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 8 kg                                                                           |
| Insulation class      | I                                                                              |
| Protection index      | IP44                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | -                                                                              |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz<br>Integrated switch button                              |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 18 W              |
| Emission               | Indirect              |
| Max consupcion         | max 18,00 W           |
| Features LED           | LED SMD               |
| CCT                    | 3000 K                |
| Duration LED (t. 25°C) | 30000 h               |
| CRI                    | > 80                  |
| Light beam             | 115°                  |
| Light beam flux        | 2300 lm               |
| Useful light flux      | 1200 lm               |
| Photobiological risk   | EXEMPT                |