


## General info

## Indoor - Wall lamps



|              |                |
|--------------|----------------|
| Ean          | 8021696287652  |
| Item         | MAKE-UP AP D45 |
| Installation | Wall lamps     |
| Guarantee    | 5 years        |
| Gross weight | 1.37 kg        |
| Volume       | 0.006732 m³    |

## Technical info



|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 1 kg                                                                           |
| Insulation class      | II                                                                             |
| Protection index      | IP54                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | -                                                                              |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 12 W              |
| Emission               | Direct                |
| Max consupcion         | max 12,00 W           |
| Features LED           | LED SMD               |
| CCT                    | 3000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 80                  |
| Light beam             | 105°                  |
| Light beam flux        | 1250 lm               |
| Useful light flux      | 1050 lm               |
| Photobiological risk   | 1                     |