

## General info


## Indoor - Wall lamps



|              |                 |
|--------------|-----------------|
| Ean          | 8021696304496   |
| Item         | OZ AP DALI NERO |
| Installation | Wall lamps      |
| Guarantee    | 5 years         |
| Gross weight | 1.23 kg         |
| Volume       | 0.008712 m³     |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.8 kg                                                                         |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Dimmable, DALI / Push                                                          |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 28 W              |
| Emission               | Diffuse               |
| Max consupcion         | max 28 W              |
| Features LED           | LED SMD               |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 30000 h               |
| CRI                    | > 80                  |
| Light beam flux        | 2500 lm               |
| Useful light flux      | 1060 lm               |
| Photobiological risk   | 1                     |
| Standby power          | < 0.50 W              |